

Bruck Bulk Plus

Anwendung: Magazines, catalogues, supplements, direct mail, inserts/flyers

Produktfamilie: Norcote

Druckverfahren: Heat set web offset

Characterization data: Fogra 45L

Oberfläche: Matt

Hersteller: Bruck

Grundlegende Merkmale	ISO		Bulk Plus			
			Bulk Plus	Bulk Plus	Bulk Plus	Bulk Plus
Flächenbezogene Masse	(ISO 536)	(g/m ²)	60	70	80	90
Dicke	(ISO 534)	(µm)	72	84	96	108
Spez. Volumen	(ISO 534)	(cm ³ /g)	1.2	1.2	1.2	1.2
Weisse, D65/10 (UV)	(ISO 2470)	(%)	95	97	98	98
Weisse CIE	(ISO 11475)	(%)	115	120	125	125
L*	(ISO 5631-2)	(D65/10°)	93	94	95	95
a*	(ISO 5631-2)	(D65/10°)	0.5	0.9	0.9	0.9
b*	(ISO 5631-2)	(D65/10°)	-7.8	-8.3	-8.3	-8.8
Opazität	(ISO 2471)	(%)	93	94	95	97
Glanz (Lehmann)	(ISO 8254-1) (Tappi T480)	(%)	8	8	8	8

Last Updated: 20/03/2026