

Bruck Norcote Bulk

End use: Magazines, catalogues, supplements, direct mail, inserts/flyers

Product Family: Norcote

Printing method: Heat set web offset

Characterization data: Fogra 45L

Finish: Matt

Producer: Bruck

Basic properties ISO

			Bulk	Bulk	Bulk	Bulk	Bulk	Bulk	Bulk
Basis Weight	(ISO 536)	(g/m ²)	48	54	57	60	65	70	80
Thickness	(ISO 534)	(µm)	58	65	68	72	78	84	96
Bulk	(ISO 534)	(cm ³ /g)	1.2	1.2	1.2	1.2	1.2	1.2	1.2
Brightness D65	(ISO 2470)	(%)	85	88	88	88	90	90	90
CIE Whiteness	(ISO 11475)	(%)	100	105	101	103	108	108	108
L-value D65	(ISO 5631-2)	(D65/10°)	91	93	93	93	94	93	93
a-value D65	(ISO 5631-2)	(D65/10°)	0.2	0.2	0.2	0.2	0.5	0.8	0.5
b-value D65	(ISO 5631-2)	(D65/10°)	-3.5	-4.2	-4.2	-4.5	-5.5	-5.6	-5.6
Opacity	(ISO 2471)	(%)	90	91	93	93	94	94	96
Gloss (Lehmann)	(ISO 8254-1) (Tappi T480)	(%)	8	8	10	8	10	8	10

Last Updated: 20/03/2026