

Bruck Norcote Bulk

Anwendung: Magazines, catalogues, supplements, direct mail, inserts/flyers

Produktfamilie: Norcote

Druckverfahren: Heat set web offset

Characterization data: Fogra 45L

Oberfläche: Matt

Hersteller: Bruck

Grundlegende Merkmale	ISO		Bulk							
			Bulk	Bulk	Bulk	Bulk	Bulk	Bulk	Bulk	Bulk
Flächenbezogene Masse	(ISO 536)	(g/m ²)	48	54	57	60	65	70	80	
Dicke	(ISO 534)	(µm)	58	65	68	72	78	84	96	
Spez. Volumen	(ISO 534)	(cm ³ /g)	1.2	1.2	1.2	1.2	1.2	1.2	1.2	
Weisse, D65/10 (UV)	(ISO 2470)	(%)	85	88	88	88	90	90	90	
Weisse CIE	(ISO 11475)	(%)	100	105	101	103	108	108	108	
L*	(ISO 5631-2)	(D65/10°)	91	93	93	93	94	93	93	
a*	(ISO 5631-2)	(D65/10°)	0.2	0.2	0.2	0.2	0.5	0.8	0.5	
b*	(ISO 5631-2)	(D65/10°)	-3.5	-4.2	-4.2	-4.5	-5.5	-5.6	-5.6	
Opazität	(ISO 2471)	(%)	90	91	93	93	94	94	96	
Glanz (Lehmann)	(ISO 8254-1) (Tappi T480)	(%)	8	8	10	8	10	8	10	

Last Updated: 20/03/2026