

Bruck Norcote Super

Anwendung: Magazines, catalogues, supplements, direct mail, inserts/flyers

Produktfamilie: Norcote

Druckverfahren: Heat set web offset

Characterization data: Fogra 45L

Oberfläche: Gloss

Hersteller: Bruck

Grundlegende Merkmale	ISO									
Flächenbezogene Masse	(ISO 536)	(g/m ²)	54*	57	60	65	70	75	80	90
Dicke	(ISO 534)	(µm)	51	52	53	55	58	62	67	75
Spez. Volumen	(ISO 534)	(cm ³ /g)	0.94	0.91	0.88	0.85	0.83	0.83	0.84	0.83
Weisse, D65/10 (UV)	(ISO 2470)	(%)	86	86	87	88	89	90	90	91
Weisse CIE	(ISO 11475)	(%)	99	101	102	104	105	107	107	108
L*	(ISO 5631-2)	(D65/10°)	92	92	92	92	92	93	93	94
a*	(ISO 5631-2)	(D65/10°)	0	0	0.2	0.6	0.6	0.7	0.6	0.7
b*	(ISO 5631-2)	(D65/10°)	-4	-4.5	-4.5	-4.8	-5.0	-5.3	-5.0	-5.5
Opazität	(ISO 2471)	(%)	90	92	92	93	94	94	95	96
Glanz (Lehmann)	(ISO 8254-1) (Tappi T480)	(%)	35	40	43	46	50	50	50	50
Glätte	(ISO 8791-4)	(µm)	1.3	1.3	1.2	1.2	1.2	1.2	1.2	1.2

Last Updated: 28/04/2026