

Bruck Norcote

Anwendung: Magazines, catalogues, supplements, direct mail, inserts/flyers

Produktfamilie: Norcote

Druckverfahren: Heat set web offset

Characterization data: Fogra 46

Oberfläche: Gloss

Hersteller: Bruck

Grundlegende Merkmale	ISO									
Flächenbezogene Masse	(ISO 536)	(g/m ²)	51	54	57	60	65	70	80	
Dicke	(ISO 534)	(µm)	49	51	52	53	56	58	66	
Volumen	(ISO 534)	(kg/m ³)	0.96	0.94	0.91	0.88	0.86	0.83	0.83	
Weisse, D65/10 (UV)	(ISO 2470)	(%)	76	77	77	77	78	78	80	
Weisse CIE	(ISO 11475)	(%)	69	72	72	72	73	73	76	
L*	(ISO 5631-2)	(D65/10°)	90	91	91	91	92	92	92	
a*	(ISO 5631-2)	(D65/10°)	-0.4	-0.2	-0.2	-0.2	-0.2	-0.2	-0.2	
b*	(ISO 5631-2)	(D65/10°)	1.5	1.3	1.3	1.3	1.3	1.3	1.3	
Opazität	(ISO 2471)	(%)	90	91	92	93	93	93	95	
Glanz (Lehmann)	(ISO 8254-1) (Tappi T480)	(%)	32	35	40	45	48	50	51	
Glätte	(ISO 8791-4)	(µm)	1.3	1.3	1.3	1.2	1.2	1.2	1.2	

Last Updated: 28/04/2026