

# Saugbrugs NorSC Lite

**End use:** Magazines, inserts, catalogues, direct mail and door drop.

**Product Family:** SC

**Product Family:** Nor

**Printing method:** Heatset & Rotogravure

**Characterization data:** Fogra 40

**Finish:** Gloss

**Producer:** Saugbrugs

Basic properties	ISO								
Basis Weight	(ISO 536)	(g/m <sup>2</sup> )	37*	39	42	45	47.4	52	56
Thickness	(ISO 534)	(μm)	40	43	47	49	50	53	55
Density	(ISO 534)	(kg/m <sup>3</sup> )	890	900	900	900	940	970	1000
Bulk	(ISO 534)	(cm <sup>3</sup> /g)	1.1	1.1	1.1	1.1	1.05	1.05	1.0
Brightness D65	(ISO 2470)	(%)	69	69	69	69	69	69	69
CIE Whiteness	(ISO 11475)	(%)	52	52	52	52	52	52	52
L-value D65	(ISO 5631-2)	(D65/10°)	88	88	88	88	88	88	88
a-value D65	(ISO 5631-2)	(D65/10°)	-1.4	-1.4	-1.4	-1.4	-1.4	-1.4	-1.4
b-value D65	(ISO 5631-2)	(D65/10°)	4.3	4.3	4.3	4.3	4.3	4.3	4.3
Opacity	(ISO 2471)	(%)	89	90	91	92	93	93	94
Gloss Hunter	(ISO 8254-1)	(%)	37	37	37	37	39	39	39
Smoothness PPS 10	(ISO 8791-4)	(μm)	1.3	1.3	1.3	1.2	1.2	1.1	1.1

*Last Updated: 14/10/2025*