

# Saugbrugs NorSC Lite

**Anwendung:** Magazines, inserts, catalogues, direct mail and door drop.

**Product Family:** SC

**Produktfamilie:** Nor

**Druckverfahren:** Heatset & Rotogravure

**Characterization data:** Fogra 40

**Oberfläche:** Gloss

**Hersteller:** Saugbrugs

Grundlegende Merkmale	ISO									
Flächenbezogene Masse	(ISO 536)	(g/m <sup>2</sup> )	37*	39	42	45	47.4	52	56	
Dicke	(ISO 534)	(µm)	40	43	47	49	50	53	55	
Blattdichte	(ISO 534)	(kg/m <sup>3</sup> )	890	900	900	900	940	970	1000	
Spez. Volumen	(ISO 534)	(cm <sup>3</sup> /g)	1.1	1.1	1.1	1.1	1.05	1.05	1.0	
Weisse, D65/10 (UV)	(ISO 2470)	(%)	69	69	69	69	69	69	69	
Weisse CIE	(ISO 11475)	(%)	52	52	52	52	52	52	52	
L*	(ISO 5631-2)	(D65/10°)	88	88	88	88	88	88	88	
a*	(ISO 5631-2)	(D65/10°)	-1.4	-1.4	-1.4	-1.4	-1.4	-1.4	-1.4	
b*	(ISO 5631-2)	(D65/10°)	4.3	4.3	4.3	4.3	4.3	4.3	4.3	
Opazität	(ISO 2471)	(%)	89	90	91	92	93	93	94	
Glanz (Hunter)	(ISO 8254-1)	(%)	37	37	37	37	39	39	39	
Glätte	(ISO 8791-4)	(µm)	1.3	1.3	1.3	1.2	1.2	1.1	1.1	

*Last Updated: 14/10/2025*