

Saugbrugs NorSC Polar

Anwendung: Magazines, inserts, catalogues, direct mail and door drop.

Product Family: SC

Produktfamilie: Nor

Druckverfahren: Heatset & Rotogravure

Characterization data: Fogra 40

Oberfläche: Gloss

Hersteller: Saugbrugs

Grundlegende Merkmale ISO

Flächenbezogene Masse	(ISO 536)	(g/m ²)	42*	47.4	51	54	57	60	65*
Dicke	(ISO 534)	(µm)	47	50	53	54	55	58	62
Blattdichte	(ISO 534)	(kg/m ³)	900	930	950	960	1020	1020	1020
Spez. Volumen	(ISO 534)	(cm ³ /g)	1.1	1.05	1.05	1.0	1.0	1.0	1.0
Weisse, D65/10 (UV)	(ISO 2470)	(%)	75	78	80	80	80	80	80
Weisse CIE	(ISO 11475)	(%)	74	77	78	78	78	78	78
L*	(ISO 5631-2)	(D65/10°)	89	89	89	89	89	89	89
a*	(ISO 5631-2)	(D65/10°)	0.1	0.1	0.1	0.1	0.1	0.1	0.1
b*	(ISO 5631-2)	(D65/10°)	-0.8	-0.8	-0.8	-0.8	-0.8	-0.8	-0.8
Opazität	(ISO 2471)	(%)	89	91	92	93	94	95	96
Glanz (Hunter)	(ISO 8254-1)	(%)	37	40	40	40	40	40	40
Glätte	(ISO 8791-4)	(µm)	1.20	1.20	1.20	1.20	1.20	1.20	1.20

Last Updated: 03/12/2024