

Saugbrugs Nor Opaq

Anwendung: Magazines, inserts, catalogues, direct mail and door drop.

Product Family: UMI

Produktfamilie: Nor

Druckverfahren: Heatset & Rotogravure

Characterization data:

Heatset: Fogra 40L

Gravure: ICC Paper profile - PSR_MF_V2_M1.icc

Oberfläche: Silk

Hersteller: Saugbrugs

Grundlegende Merkmale	ISO				
Flächenbezogene Masse	(ISO 536)	(g/m ²)	42	45H	52
Dicke	(ISO 534)	(µm)	53	55	57
Blattdichte	(ISO 534)	(kg/m ³)	800	820	910
Spez. Volumen	(ISO 534)	(cm ³ /g)	1.25	1.22	1.10
Weisse, D65/10 (UV)	(ISO 2470)	(%)	68	68	68
Weisse CIE	(ISO 11475)	(%)	50	50	50
L*	(ISO 5631-2)	(D65/10°)	87	87	87
a*	(ISO 5631-2)	(D65/10°)	-1.4	-1.4	-1.4
b*	(ISO 5631-2)	(D65/10°)	4.5	4.5	4.5
Opazität	(ISO 2471)	(%)	93	94	97
Glanz (Hunter)	(ISO 8254-1)	(%)	20-25	20-25	20-25
Glätte	(ISO 8791-4)	(µm)	1.7	1.7	1.7

Last Updated: 01/02/2023