

# Skogn Norbright 68

**End use:** Newspapers, direct mail, free-sheets, directories, supplements, inserts/flyers, magazines, books

**Product Family:** Norbright 62/65/, Norbright Plus

**Printing method:** Cold set web offset / (Heat set web offset)

**Finish:** Matt

**Producer:** Skogn

Basic properties	ISO					
Basis Weight	(ISO 536)	(g/m <sup>2</sup> )	45	48.8	52	55
Thickness	(ISO 534)	(µm)	66	70	74	79
Density	(ISO 534)	(kg/m <sup>3</sup> )	670	680	690	690
Bulk	(ISO 534)	(cm <sup>3</sup> /g)	1.5	1.5	1.4	1.4
Roughness (Bendtsen)	(ISO 8791-2)	(ml/min)	125	130	130	130
Brightness D65	(ISO 2470)	(%)	68	68	68	68
L-value D65	(ISO 5631-2)	(D65/10°)	87	87	87	87
a-value D65	(ISO 5631-2)	(D65/10°)	-0.3	-0.3	-0.3	-0.3
b-value D65	(ISO 5631-2)	(D65/10°)	3.5	3.5	3.5	3.5
Opacity	(ISO 2471)	(%)	91	92	93	94

*Last Updated: 10/10/2023*