

Skogn Norbright 68

Anwendung: Newspapers, direct mail, free-sheets, directories, supplements, inserts/flyers, magazines, books

Produktfamilie: Norbright 62/65/, Norbright Plus

Druckverfahren: Cold set web offset / (Heat set web offset)

Oberfläche: Matt

Hersteller: Skogn

Grundlegende Merkmale	ISO						
Flächenbezogene Masse	(ISO 536)	(g/m ²)	45	48.8	52	55	
Dicke	(ISO 534)	(µm)	66	70	74	79	
Blattdichte	(ISO 534)	(kg/m ³)	670	680	690	690	
Spez. Volumen	(ISO 534)	(cm ³ /g)	1.5	1.5	1.4	1.4	
Rauhigkeit (Bendtsen)	(ISO 8791-2)	(ml/min)	125	130	130	130	
Weisse, D65/10 (UV)	(ISO 2470)	(%)	68	68	68	68	
L*	(ISO 5631-2)	(D65/10°)	87	87	87	87	
a*	(ISO 5631-2)	(D65/10°)	-0.3	-0.3	-0.3	-0.3	
b*	(ISO 5631-2)	(D65/10°)	3.5	3.5	3.5	3.5	
Opazität	(ISO 2471)	(%)	91	92	93	94	

Last Updated: 10/10/2023