

# Skogn Norbright Plus

**End use:** Newspapers, direct mail, free-sheets, directories, supplements, inserts/flyers, magazines, books

**Product Family:** Norbright 62/65/68

**Printing method:** Cold set web offset / (Heat set web offset)

**Finish:** Matt

**Producer:** Skogn

Basic properties	ISO							
Basis Weight	(ISO 536)	(g/m <sup>2</sup> )	45	48.8	52	55	60	
Thickness	(ISO 534)	(µm)	66	70	74	79	86	
Density	(ISO 534)	(kg/m <sup>3</sup> )	670	680	690	690	700	
Bulk	(ISO 534)	(cm <sup>3</sup> /g)	1.5	1.5	1.4	1.4	1.4	
Roughness (Bendtsen)	(ISO 8791-2)	(ml/min)	125	130	130	130	130	
Brightness D65	(ISO 2470)	(%)	72	72	72	72	72	
L-value D65	(ISO 5631-2)	(D65/10°)	87	87	87	87	87	
a-value D65	(ISO 5631-2)	(D65/10°)	0.3	0.3	0.3	0.3	0.3	
b-value D65	(ISO 5631-2)	(D65/10°)	0	0	0	0	0	
Opacity	(ISO 2471)	(%)	91	92	93	94	95	

*Last Updated: 03/10/2023*