

# Skogn Norbright Plus

**Anwendung:** Newspapers, direct mail, free-sheets, directories, supplements, inserts/flyers, magazines, books

**Produktfamilie:** Norbright 62/65/68

**Oberfläche:** Matt

**Druckverfahren:** Cold set web offset / (Heat set web offset)

**Hersteller:** Skogn

Grundlegende Merkmale	ISO						
Flächenbezogene Masse	(ISO 536)	(g/m <sup>2</sup> )	45	48.8	52	55	60
Dicke	(ISO 534)	(µm)	66	70	74	79	86
Blattdichte	(ISO 534)	(kg/m <sup>3</sup> )	670	680	690	690	700
Spez. Volumen	(ISO 534)	(cm <sup>3</sup> /g)	1.5	1.5	1.4	1.4	1.4
Rauhigkeit (Bendtsen)	(ISO 8791-2)	(ml/min)	125	130	130	130	130
Weisse, D65/10 (UV)	(ISO 2470)	(%)	72	72	72	72	72
L*	(ISO 5631-2)	(D65/10°)	87	87	87	87	87
a*	(ISO 5631-2)	(D65/10°)	0.3	0.3	0.3	0.3	0.3
b*	(ISO 5631-2)	(D65/10°)	0	0	0	0	0
Opazität	(ISO 2471)	(%)	91	92	93	94	95

Last Updated: 03/10/2023